

LED VAPOR TIGHT



Garage Lighting Solution

Linear LED vapor tight light fixtures can be built with wattage & CCT selectable switch to reduce stocking inventory. And this led fixture is powerful lighting in harsh environments, protecting the light source from dust and moisture.



Shatter-proof
Housing



High Efficacy
150 LPW



CCT & Wattage
Selectable



Impact Rated
IK08



IP65 Rating
Waterproof




FEATURE

Style	Vapor Tight
Housing	5VA Rated ABS
Diffuser	V0 Rated PC, Shatter-Proof
Waterproof	IP65
Lumen Efficacy	150 LPW (Clear), 140 LPW (Frosty)
Input Power & CCT	Selectable
Sensor	Microwave motion/photocell
Warranty	5 Years
Beam Angle	120 deg.
Emergency Backup	UL924, CEC Title-20
Listed	DLC, ETL/cETL, CE, RoHS



SPECIFICATION

Model#	Input Voltage	Wattage	Lumen Efficacy	CCT	CRI	Length
LT-TPA220	100-277VAC	Selectable 16W-20W-25W	150 LPW	Selectable 30K-40K-50K, Can be a single CCT	80	2'
LT-TPA436	100-277VAC	Selectable 20W-30W-40W	150 LPW		80	4'
LT-TPA440	100-277VAC	Selectable 32W-40W-50W	150 LPW		80	4"
LT-TPA880	100-277VAC	Selectable 60W-70W-80W	150 LPW		80	8'
LT-TPA810	100-277VAC	Selectable 80W-90W-100W	130 LPW		80	8'



CCT &
Wattage
Selectable



Motion
Sensor
Available



Intelligen
t Battery
Option

CERTIFICATE



ORDER INFO.

Com.	Series	Size	Power Code	CCT	Input Voltage	Control	Duration (EM)	Diffuser
LT	TPA	2	20	27K=2700K	Std.=100-277VAC	DM=1-10DC Dim	Std.=90 minutes	Blank= Frosty
		4	36	30K=3000K	HV= 200-480VAC	DA= Dali Dim	2H=120 minutes	C=Clear
		40	40	40K=4000K	MV=120-347VAC	EM=Emergency Kit	3H=180 minutes	
				50K=5000K		PC=Photocell		
		8	80	57K=5700K		MS=Motion Sensor		
		10		CPT=Selectable 30K-40K-50K				