






# ROUND LED HIGH BAY



## Motion Sensor

UFO led high bay lights feature IP66 rated and used across various environments, including industrial facilities, manufacturing plants, big box retail centers, and even school swimming pools.

 Motion Sensor	 High Efficacy 160 LPW	 Emergency Backup Option	 Excellent Heat Sink System	 IP66 Rating Waterproof
--	---	--	--	---

## FEATURE

Style	Motion Sensor
Housing	Aluminum Alloy
Diffuser	Shatter-proof PC
Waterproof	IP65
Lumen Efficacy	160 LPW
Color Temperature	3000K, 4000K, 5000K, 5700K
Sensor	Microwave motion/photocell
Emergency Backup Available	Field Assembly
Listed	ETL/cETL, CE, RoHS
Warranty	5 Years
Beam Angle	60/90/120 deg.

## SPECIFICATION

Model#	Input Voltage	Power	Light Efficacy	Motion Sensor	Dimension	Equv.
LT-SBA100W	100-277VAC	100W	160 LPW	Available	Φ253x165 mm	400W MH
LT-SBA150W	100-277VAC	150W	160 LPW	Available	Φ308x176 mm	600W MH
LT-SBA200W	100-277VAC	200W	160 LPW	Available	Φ354x179 mm	1000W MH
LT-SBA240W	100-277VAC	240W	160 LPW	Available	Φ405x179 mm	1000W MH
LT-SBA300W	100-277VAC	300W	160 LPW	Available	Φ405x179 mm	1000W MH



## Excellent Heat Sink System Design

The heat sink dissipation design is considering the analysis of thermodynamic cycle. The new design is more compact without sacrificing performance.

## Optional Emergency Backup

Assembled an UL924 & CE certified battery in the field, they can guide people out of the building in time under power outages, blackouts, fires, and lightning strikes, etc.



## CERTIFICATE



## ORDER INFO.

Com.	Series	Power	Input Voltage	CCT	Control	Duration (EM)
LT	SBA	100W	Std.=100-277vac	27K=2700K	DM=1-10DC Dim	Std.= 90minutes
		150W	HV= 200-480VAC	30K=3000K	DA= Dali Dim	2H= 120 minutes
		200W		40K=4000K	PS=Photocell	3H= 180 minutes
		240W		50K=5000K	MS=Motion Sensor	
		300W		57K=5700K	EM=Emergency Kit	
					EMH=Emergency Kit	